

XD3-6KTL

Single Phase Hybrid Inverter

Residential



Efficient Higher Revenue

- Max. Efficiency 97.5%
- Max. PV Input Voltage 600V
- 150% Peak Output Power
- 2 MPP Trackers, 150% DC Input Oversizing
- Max. PV Input Current 16A, Compatible with High Power Modules

Intelligent Simple O&M

- IP66 Protection Degree: support outdoor installation
- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- DC & AC Type II SPD: prevent lightning damage
- Battery Reverse Connection Protection

Flexible Abundant Configuration

- Plug & Play, EPS Switching Under 10ms
- Compatible with Lead-acid and Lithium Batteries
- Supports multiple units in parallel
- AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

	XD3KTL	XD3K6TL	XD4KTL	XD4K6TL	XD5KTL	XD6KTL
Input (PV)						
Max. PV Input Power	4.5kW	5.4kW	6kW	6.9kW	7.5kW	9kW
Max. PV Input Voltage	600V					
Start-up Voltage	100V					
Rated Voltage	360V					
MPPT Voltage Range	100V ~ 550V					
Number of MPP Trackers	2					
Number of String per MPPT	1 / 1					
Max. Current per MPPT	16A					
Max. Short Circuit Current per MPPT	24A					
Output (AC)						
Rated Output Power	3kVA	3.68kVA	4kVA	4.6kVA	5kVA	6kVA
Max. Output Power	3.3kVA	3.68kVA	4.4kVA	4.6kVA	5.5kVA	6kVA
Max. Output Current	15A	16A	20A	20.9A	22.7A	27.3A
Rated Voltage	230V					
Rated Frequency	50Hz / 60Hz					
THDi(@Rated Power)	< 3%					
Power Factor	0.8 leading ~ 0.8 lagging					
Output (EPS)						
Max. Output Power	3kVA	3.68kVA	4kVA	4.6kVA	5kVA	6kVA
Max. Output Current	15A	16A	20A	20.9A	22.7A	27.3A
Peak Output Power, Time	4.5kW, 10s	5.5kW, 10s	6kW, 10s	6.9kW, 10s	7.5kW, 10s	7.5kW, 10s
Rated Voltage, Frequency	230V, 50Hz					
THDv (@Rated Power)	< 3%					
Switch Time	< 10ms					
Battery						
Battery Type	Lithium, Lead-acid					
Battery Voltage Range	40V ~ 60V					
Max. Charge / Discharge Current	100A					
Communication	CAN					
Efficiency						
Max. Efficiency	97.50%					
EU Efficiency	97.20%					
Battery Charge / Discharge Efficiency	95.00%					
Protection						
DC Switch	Yes					
DC Reverse Polarity Protection	Yes					
Anti-islanding Protection	Yes					
AC Short Circuit Protection	Yes					
Residual Current Monitoring	Yes					
Insulation Resistance Monitoring	Yes					
Ground Fault Monitoring	Yes					
Over Current / Voltage Protection	Yes					
Battery Soft Start Protection	Yes					
Surge Protection	Type II					
AFCI Protection	Optional					
Communication						
Display	LCD					
Communication	RS485 / CAN / WIFI / 4G / LAN / Bluetooth					
Standard Compliance						
Certification	IEC/EN 62109-1/2, IEC/EN 61000-6-1/3, IEC61727/IEC62116, EN50549, CEI0-21, C10/C11, VDE4105, VDE0126, G98/99, RD244, UNE217001, UNE217002, AS4777, NRS097-2-1					
General Data						
Dimension (W x H x D)	481 x 390 x 200 mm					
Weight	21.35 kg					
Operating Temperature Range	-30°C ~ +60°C					
Cooling Method	Natural					
Protection Degree	IP66					
Max. Operating Altitude	4000m					
Relative Humidity	0~100%					
Self-consumption	< 10W					
Topology	High Frequency Insolation (For battery)					